

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for transmission of packetized data in a wireless communication system having a designated packet error rate, the method comprising:
determining a first number of installments for transmission of a first subpacket of data;
determining a second number of installments for transmission of the first subpacket of data, the second number less than the first number;
determining power boost gain factors for the second number of installments, the power boost gain factors satisfying the designated packet error rate;
power boosting transmissions of ~~a~~the second number of installments of the first subpacket of data by applying the power boost gain factors, ~~wherein the second number is less than the first number, wherein the second number is selected to satisfy the designated packet error rate;~~ and
terminating transmission of the first subpacket of data after the second number of installments.
2. (Canceled)
3. (Currently Amended) The method as in claim 2-1, wherein the power boosting gain ~~factor~~ is factors are nominally set to (N/M) , wherein N is the first number of installments, and M is the second number of installments.
4. (Original) The method as in claim 1, wherein terminating transmission of the first subpacket of data comprises:
initiating a second subpacket of data after the second number of installments.

5. (Previously Presented) The method as in claim 1, wherein the first number of installments for the first subpacket of data corresponds to a first time period, wherein terminating transmission of the first subpacket of data comprises:

waiting for expiration of the first time period; and
initiating transmission of a second subpacket of data after expiration of the first time period.

6. (Original) The method as in claim 1, further comprising:

receiving a negative acknowledgement message after transmission of the second number of installments; and
processing the first subpacket of data at a higher layer.

7. (Original) The method as in claim 1, further comprising:

receiving an acknowledgement message before transmission of all of the second number of installments; and
initiating transmission of a second subpacket of data.

8. (Currently Amended) An apparatus for transmission of packetized data in a wireless communication system having a designated packet error rate, the apparatus comprising:

means for determining a first number of installments for transmission of a first subpacket of data;

means for determining a second number of installments for transmission of the first subpacket of data, the second number less than the first number;

means for determining power boost gain factors for the second number of installments, the power boost gain factors satisfying the designated packet error rate;

means for power boosting transmissions of ~~a~~the second number of installments of the first subpacket of data by applying the power boost gain factors, ~~wherein the second number is less than the first number, wherein the second number is selected to satisfy the designated packet error rate;~~ and

means for terminating transmission of the first subpacket of data after the second number of installments.

9. (Canceled)

10. (Currently Amended) The apparatus as in claim 9-8, wherein the power boosting gain ~~factor is factors~~ are nominally set to (N/M) , wherein N is the first number of installments, and M is the second number of installments.

11. (Original) The apparatus as in claim 8, wherein means for terminating transmission of the first subpacket of data comprises:

means for initiating a second subpacket of data after the second number of installments.

12. (Previously Presented) The apparatus as in claim 8, wherein the first number of installments for the first subpacket of data corresponds to a first time period, wherein means for terminating transmission of the first subpacket of data comprises:

means for waiting for expiration of the first time period; and

means for initiating transmission of a second subpacket of data after expiration of the first time period.

13. (Original) The apparatus as in claim 8, further comprising:

means for receiving a negative acknowledgement message after transmission of the second number of installments; and

means for processing the first subpacket of data at a higher layer.

14. (Original) The apparatus as in claim 8, further comprising:

means for receiving an acknowledgement message before transmission of all of the second number of installments; and

means for initiating transmission of a second subpacket of data.

15. (Currently Amended) A base station apparatus comprising:
a packet processing unit adapted to receive data for transmission and generate subpackets,
each of the subpackets transmitted in a number of installments;
a power boost unit adapted to:
determine a portion of the installments to which to apply a power boost, and
apply a-the power boost factor to a-the portion of the-subpackets installments;
an acknowledgement message processing unit adapted to terminate transmission of
installments for a subpacket on receipt of an acknowledgement message; and
a transmitter for transmitting power boosted-subpackets installments, wherein the packet
processing unit terminates processing of the subpacket transmission of the
installments on receipt of a negative acknowledgement message after the portion
of the subpackets-installments is transmitted.
16. (Original) A method for transmission from a mobile station in a wireless communication
system, wherein each data packet received is transmitted in a number of installments, the method
comprising:
transmitting a first negative acknowledgement message for a last installment of a first
subpacket, the first negative acknowledgement transmitted at a first time slot; and
transmitting a second negative acknowledgement message for the last installment of the
first subpacket, the second negative acknowledgement transmitted at a second
time slot, wherein the second time slot is designated for the first subpacket of the
next packet.
17. (Original) The method as in claim 16, wherein the first negative acknowledgement has a
first bit pattern, and the second negative acknowledgement is a different bit pattern
orthogonal to the first bit pattern.
18. (Original) An apparatus for transmission from a mobile station in a wireless
communication system, wherein each data packet received is transmitted in a number of
installments, the apparatus comprising:

means for transmitting a first negative acknowledgement message for a last installment of a first subpacket, the first negative acknowledgement transmitted at a first time slot; and

means for transmitting a second negative acknowledgement message for the last installment of the first subpacket, the second negative acknowledgement transmitted at a second time slot, wherein the second time slot is designated for the first subpacket of the next packet.

19. (Currently Amended) A computer-program product for transmitting packetized data in a wireless communication system having a designated packet error rate, the computer-program product comprising a computer readable medium having instructions thereon, the instructions comprising:

code for determining a first number of installments for transmission of a first subpacket of data;

code for determining a second number of installments for transmission of the first subpacket of data, the second number less than the first number;

code for determining power boost gain factors for the second number of installments, the power boost gain factors satisfying the designated packet error rate;

code for power boosting transmissions of ~~a~~ the second number of installments of the first subpacket of data by applying the power boost gain factors, ~~wherein the second number is less than the first number, wherein the second number is selected to satisfy the designated packet error rate;~~ and

code for terminating transmission of the first subpacket of data after the second number of installments.

20. (Previously Presented) A computer-program product for transmission from a mobile station in a wireless communication system, the computer-program product comprising a computer readable medium having instructions thereon, the instructions comprising:

code for transmitting a first negative acknowledgement message for a last installment of a first subpacket, the first negative acknowledgement transmitted a first time slot; and

code for transmitting a second negative acknowledgement message for the last installment of the first subpacket, the second negative acknowledgement transmitted at a second time slot, wherein the second time slot is designated for the first subpacket of the next packet.